

Sescom P/DXLM-F Digital Audio Plenum Cable 3-Pin XLR & Microphone Cables

FEATURES

- Assembled with Belden 82761 Plenum Audio Cable & Neutrik XLR Connectors
- Suitable for Use in Ducts, Plenums & Other Spaces Used for Environmental Air with No Conduit
- Fire-Resistant and Low Smoke Producing
- Built for Rugged Connectivity
- High Quality Components
- Handcrafted in the US
- 1 Year Warranty



SPECIFICATIONS

Cable: Belden 82761	Single Pair, 2 Conductor 22AWG
Stranding	7X30
Conductor Material	Tinned Copper
Insulation Material	FEP – Fluorinated Ethylene Propylene
Outer Shield Material Trade	Bedfoil (Z-Fold)
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Jacket Material Trade	Flamarrest
Outer Jacket Material	LS PVC – Low Smoke Polyvinyl Chloride
Plenum	Yes
Non-Plenum Number	BL-8761
UL Voltage Rating	300 V (CMP)
Available Lengths	6, 10, 15, 25, 50, 75, 100, 150, 200, 300
Connectors: Neutrik NC3MXX / NC3FXX	3-Pin XLR Male to 3-Pin XLR Female Zinc Diecast Shell Internal Thread on Shell is Protected Against Damage Improved Chuck-Type Strain Relief Boot Reduces Cable Bending Stresses

