

4 Channel Passive Balanced Audio Extender



Specifications

- 12- Inch Fanouts
- Neutrik 3-Pin XLR & Locking RJ45 etherCON Connectors
- Digital Audio 48k 24bit AES/EBU Transmission Distance: 1000 feet
- Analog Balance Line Level Audio Transmission Distance: 2000 feet
- Mic Level Audio Transmission Distance: 2000 Feet
- AES72 Type 20

Features:

- Send 4 Channels of Analog or Digital Audio, AES/EBU or DMX over Cat 5/6/7 Cable
- 3 Channel Versions Support Phantom Power - 48V
- 4 Channel Versions Support Phantom Power -48V - REQUIRES Shielded Category cable
- Replaces Bulky Multichannel Audio Snakes Allowing for Quick Setup
- Passive Design Requires No Power
- Compact & Lightweight - Easy to Store
- Rugged Road Ready Black Aluminum Enclosed

Sescom Passive Balanced Audio Extenders Over CAT5/6/7		Wired to the EIA/TIA 568B standard	
4-channel			
<i>etherCON NE8FDX-Y6 pin</i>	<i>Conductor color code</i>	<i>Channel</i>	<i>XLR Pin</i>
1	white/orange stripe	CH2+	PIN2
2	orange solid	CH2-	PIN3
3	white/green stripe	CH3+	PIN2
4	blue solid	CH1-	PIN3
5	white/blue stripe	CH1+	PIN2
6	green solid	CH3-	PIN3
7	white/brown stripe	CH4+	PIN2
8	brown solid	CH4-	PIN3
<i>ALL XLR PINS 1 TIE TO SHELL</i>			
3-channel			
<i>etherCON NE8FDX-Y6 pin</i>	<i>Conductor color code</i>	<i>Channel</i>	<i>XLR Pin</i>
1	white/orange stripe	CH2+	PIN2
2	orange solid	CH2-	PIN3
3	white/green stripe	CH3+	PIN2
4	blue solid	CH1-	PIN3
5	white/blue stripe	CH1+	PIN2
6	green solid	CH3-	PIN3
7	white/brown stripe	<i>ALL XLR PINS 1</i>	
8	brown solid	<i>ALL XLR PINS 1</i>	

