

8 Channel Passive Balanced Audio over CAT Extenders



FEATURES:

- Send 8 Channels of Analog or Digital Audio, AES/EBU or DMX over 2 Cat 5/6/7 Cables
- Supports Phantom Power - 48V - **REQUIRES Shielded Category cables**
- Replaces Bulky Multichannel Audio Snakes
- Passive Design Requires No Power
- Easily Transported and Stored
- Rugged Black Aluminum Enclosures

SPECIFICATIONS:

- Neutrik 3-Pin XLR & Locking RJ45 etherCON Connectors
- Digital Audio 48k 24bit AES/EBU Transmission Distance: 1000 Feet
- Analog Balance Line Level Audio Transmission Distance: 2000 Feet
- Mic Level Audio Transmission Distance: 2000 Feet

AVAILABLE 1 TO 1 CONFIGURATIONS:

- SES-8XLRM-CATBX - SES-8XLRM-CATBX
- SES-8XLRM-CATBX - SES-8XLRF-CATBX
- SES-8X6F2M-CATBX - SES-8X6M2F-CATBX
- SES-8X2F6M-CATBX - SES-8X2M6F-CATBX
- SES-8X4F4M-CATBX - SES-8X4M4F-CATBX
- SES-8X6M2F-CATBX - SES-8X6F2M-CATBX
- SES-8X2M6F-CATBX - SES-8X2F6M-CATBX
- SES-8X4M4F-CATBX - SES-8X4F4M-CATBX

8 Channel Passive Balanced Audio over CAT Extenders

For cross compatibility configurations with our existing 4 channel CAT snakes and boxes see below:

8 CHANNEL BOX	CHANNELS	4 CHANNEL SNAKE	4 CHANNEL BOX
SES-8XLRF-CATBX	1-4	SES-4XLRM-CAT	SES-4XLRM-CATBX
	5-8	SES-4XLRM-CAT	SES-4XLRM-CATBX
SES-8XLRM-CATBX	1-4	SES-4XLRF-CAT	SES-4XLRF-CATBX
	5-8	SES-4XLRF-CAT	SES-4XLRF-CATBX
SES-8X6M2F-CATBX	1-4	SES-4XLRF-CAT	SES-4XLRF-CATBX
	5-8	SES-4X2F2M-CAT	SES-4X2F2M-CATBX
SES-8X2M6F-CATBX	1-4	SES-4X2F2M-CAT	SES-4X2F2M-CATBX
	5-8	SES-4XLRM-CAT	SES-4XLRM-CATBX
SES-8X4M4F-CATBX	1-4	SES-4XLRF-CAT	SES-4XLRF-CATBX
	5-8	SES-4XLRM-CAT	SES-4XLRM-CATBX
SES-8X6F2M-CATBX	1-4	SES-4XLRM-CAT	SES-4XLRM-CATBX
	5-8	SES-4XLR2M2F-CAT	SES-4X2M2F-CATBX
SES-8X2F6M-CATBX	1-4	SES-4XLR2M2F-CAT	SES-4X2M2F-CATBX
	5-8	SES-4XLRF-CAT	SES-4XLRF-CATBX
SES-8X4F4M-CATBX	1-4	SES-4XLRM-CAT	SES-4XLRM-CATBX
	5-8	SES-4XLRF-CAT	SES-4XLRF-CATBX

