

SCXXJA

Sescom Mic Cable Canare Star-Quad 3-Pin XLR Male to Right-Angle 3-Pin XLR Female

FEATURES:

- Canare L-4E6S Star-Quad Microphone Cable
- Neutrik 3-Pin Male & Female Right Angle XLR Connectors
- Braided Copper Shield
- Flexible in Extreme Cold Weather
- Cross Linked PE Insulation
- Reduced Handling Noise
- Rejects EMI and RFI

SPECIFICATIONS:

Neutrik 3-Pin Connectors:

- Number of Conductors: 4 (2 Blue, 2 White)
- Conductor AWG: 24
- Quad AWG: 21 (Effective AWG of combined twin conductors)
- Nom. 0.D.: 0.236"
- Jacket: PVC
- Jacket Nom. Thickness: 0.044"
- Brittle Point: -56°F
- Insulation Type: IPE
- Insulation Thickness: 15.7 MIL
- Pitch Twist Quad: 0.79"
- Shield Coverage: >95% TAC Braid
- Cond D.C.R.: <29.9 Ohm/1000 Ft
- Shield D.C.R.: <9.1 Ohm/1000 Ft
- Nom. Capacitance: 150 pF/m (between twin Blue & twin White)
- Nom. Capacitance: 185 pF/m (between conductors to shield)
- Nom. Impedance: 44 Ohm
- Nom. Atten.: 0.9 V/1000 Ft

scom

• Group Delay Time: 1.80 ns/ft

