

SES-IC2P-S

Sescom 2-Pair Intercom Cable
6 pin XLR Male to Female - for RS-702 & RS-602 Beltpacks

FEATURES:

- Intercom Cable for RS-702 & RS-602 Beltpacks
- Extremely Lightweight & Flexible Cable
- Overall PVC Jacketed for Strength and Durability
- Neutrik 6-Pin Male & Female Connectors

SPECIFICATIONS:

- **Canare MR202-2AT 2-Pair Twisted Pair Multi-Channel Cable**
 - Number of Channels: 2
 - Nominal O.D: 6.7
 - Number of Conductor: 4
 - AWG: 25
 - Conductor D.C.R: 10.7 ($\Omega/100\text{m}$)
 - Nominal Capacitance: 76 pF/m
- **Neutrik 6-Pin Male & Female Connectors**
 - Capacitance between contacts: ≤ 7 pF
 - Contact resistance: ≤ 3 m Ω
 - Dielectric strength: 1.5 kVdc
 - Insulation resistance: > 10 G Ω (initial)
 - Rated current per contact: 7.5 A
 - Rated voltage: < 50 V
 - Insertion force: ≤ 20 N
 - Withdrawal force: ≤ 20 N
 - Lifetime: > 1000 mating cycles

